



Features :

- Telcordia, TIA/EIA and JIS compliance
- Available as FC , SC , ST , LC , MTRJ , E2000
- Choice of Simplex , Duplex and Hybrid version
- High precision Zirconia or standard Phosphor bronze
- Sleeves alignment
- Choice of Metal or Plastic Housing
- Low insertion loss
- High repeatability and stability with easy installation

Application:

- Fiber distribution
- LAN / WAN / Metro and Data processing networks
- FTTX Applications
- CATV
- Testing Instruments
- Telecommunications systems

Temperature Cycling: (61300-2-18) - 40 to + 75 Deg C (≤ 0.2 dB Change)	Vibration (Mated pair): (61300-2-1) 10 55 Hz 1.5 mm P to P (≤ 0.2 dB Change)	Damp Heat: (61300-2-19) +40 Deg C at 93% RH for 96 hrs (≤ 0.4 dB Change)
High Temperature: (61300-2-18) +70 Deg C for 96 hrs (≤ 0.4 dB Change)	Mating Durability: (61300-2-2) 500 Mating cycles , clean every 25 (≤ 0.2 dB Change)	Operating Temperature: -40 to +85 Deg C

Ordering Information:

Example: ATAD-01-SX-SM
Description: ATAD FC/PC, Simplex, SM adaptor.

